

PS Series LCD Monitors

- ❑ Ultra Compact Space Saving
- ❑ Audio
- ❑ OSD (Multiple Languages)
- ❑ Picture in Picture
- ❑ High Resolution
- ❑ BNC / VGA/S-Video
- ❑ 15", 17", 19"
- ❑ Front Mounted Controls
- ❑ NTSC / PAL
- ❑ Loop Through
- ❑ 1280 x 1024



The New Range of LCD Monitors have been specifically Designed for use in with CCTV Systems, including CVBS & S-VGA Connectors, allows flexibility of use

These Monitors offer excellent image quality when used as a CCTV monitor or as a PC Monitor, using state of the art long life backlight systems. By employing this technology ensures that all images no matter what size are always displayed in full detail. One other advantage of the backlight system used is extremely long service life, without degradation found on normal CRT monitors.

LCD Monitors are ideally suited to applications of limited space, sharp images & a wide view angle ensure these monitors will be at home in any application.



PS Series LCD Monitors

	PSDT1525	PSDT1745	PSDT1945
LCD Display	15" Active Matrix	17" Active Matrix	19" Active Matrix
Resolution	500TVL	500TVL	500TVL
Contrast Ratio	400:1	500:1	550:1
Brightness	350cd/m2	420cd/m2	400cd/m2
Response Time Tr/Tf	4 / 12ms	6 / 2ms	5.6 / 2.4ms
Display Colour	262,144	16.2M	16.2M
Viewing Angle	120°	140°	140°
Lamp Life	50,000 hrs	50,000 hrs	50,000hrs
Display Mode	Video/S-Video/VGA	Video/S-Video/VGA	Video/S-Video/VGA
Connectors	BNC/15pin VGA/ RCA (Audio)	BNC/15pin VGA/ RCA (Audio)	BNC/15pin VGA/ RCA (Audio)
De Interlace	Yes	Yes	Yes
3D Comb Filter	NTSC/PAL	NTSC/PAL	NTSC/PAL
Audio Speaker	1W Max	1w Max	1W Max
Power Input / Output	12V/4A 12V/1A	12V/4A 12V/1A	12V/4A 12V/1A
Power Consumption	40W	50W	50W
Power Management	Yes	Yes	Yes
Operating Conditions	Temp 0°C- 40°C Humidity: 10% - 85%	Temp 0°C- 40°C Humidity: 10% - 85%	Temp 0°C- 40°C Humidity: 10% - 85%
Dimensions (WxHxD)	353 x 338 x 170mm	375 x 370 x 170mm	421 x 406 x 170mm
Weight	4kgs	5kgs	6.3kgs

Subject to Change without Notice